

Interchange Couplers & Tips

Quick Disconnect Couplings, Specialist Couplings



Agricultural O.E.M. Interchange Couplers and Tips



John Deere

S25-4-20 female body interchanges with the John Deere AR47331 female body and connects with the Safeway S11-4 and John Deere AR30210 male tips. Rugged ball style valving. The one-way sleeve allows implement break-away when mounted in a S25-4-20 clamp. Provided with a female 1/2" pipe thread.

S25-15-20 female body also interchanges with the John Deere AR47331, but has female 3/4"-16 ORB thread. Connects with the Safeway S11-15 and John Deere AR3010 male tips. Also uses the S42-4-20 double break-away clamp.

S11-4 and S11-15 male tips connect with the old style John Deere casting as well as the female bodies listed above. Rugged ball style valving. The S11-4 has 1/2" pipe thread and the S11-15 has 3/4"-16 ORB thread. Plated and hardened for durability.

Body O-ring - S170-4
Clamp - S42-4-20



International Harvester

S25-4-21P female body is an interchange for the I-H 544788R1 female body and connects with the Safeway S12-4 and I-H 1272770 male tips. Drip free, high flow pop-pet style valving. The one-way sleeve allows implement break-away when mounted in a S42-4-21 clamp. Provided with a female 1/2" pipe thread.

S25-16-21P female body also interchanges with the I-H 544788R1, but has female 7/8"-14 ORB thread. Connects with the Safeway S12-16 and I-H 544787R91 male tips. Also uses the S42-4-21 double break-away clamp.

S12-4 and S12-16 male tips connect with the old style I-H casting as well as the female bodies listed above. Rugged ball style valving. The S12-4 has 1/2" pipe thread and the S12-16 has 7/8"-14 ORB thread. Plated and hardened for durability.

Body O-ring - S160-4
Clamp - S42-4-21



J.I. Case

S13-4 male tip is a direct interchange for the J.I. Case old style male tip A160884. It connects with the old style J.I. Case female body 28542. Rugged ball style valving, 1/2" pipe thread. Plated and hardened for durability.