


TTS2C00

Solenoid Operated Directional Controls



TT-S2C Pilot Operated Poppet, 2 Way, Normally Open



DESCRIPTION

12 size, 1 1/16-12 thread, "Tecnod" series, solenoid operated, 2 way normally open, pilot operated poppet valve with free reverse flow energized.

OPERATION


When de-energized the TT-S2C allows flow to pass from (1) to (2), but restricts flow from (2) to (1). When energized the valve blocks flow from (1) to (2) but allows free reverse flow from (2) to (1).

OPERATION OF MANUAL OVERRIDE OPTION: To override, turn the manual override screw clockwise. To release turn the manual override screw counter-clockwise.

FEATURES


- Hardened parts for long life.
- Efficient wet-armature construction.
- Cartridges are voltage interchangeable.
- Manual override option.
- Industry common cavity.
- Unitized, molded coil design.
- Continuous duty rated solenoid.
- Optional coil voltages and terminations.
- Optional "I" Coil: Weatherproof, Thermal Shock, Immersion Safe.

HYDRAULIC SYMBOL



PERFORMANCE

Actual Test Data (Cartridges Only)



VALVE SPECIFICATIONS


Nominal Flow	30 GPM (114 LPM)
Rated Operating Pressure	3000 PSI (241 bar)
Typical Internal Leakage (150 SSU)	0-10 drops/min
Viscosity Range	36 to 3000 SSU (3 to 647 cSt)
Filtration	ISO 18/16/13
Media Operating Temperature Range	-40° to 250° F (-40° to 120° C)
Weight	.51 lbs. (.23 kg)
Operating Fluid Media	General Purpose Hydraulic Fluid
Cartridge Torque Requirements	70 ft-lbs (94.9 Nm)
Coil Nut Torque Requirements	4-6 ft-lbs (5.4-8.1 Nm)
Cavity	TECNORD 2W
Cavity Form Tool (Finishing)	40500032
Seal Kit	21191300

TTS2C00

Solenoid Operated Directional Controls



DIMENSIONS



ORDERING INFORMATION

TT-S2C

OPTIONS	
Buna Standard	00
Viton Standard	V0
Buna, Override, Knob	0K
Viton, Override, Knob	VK
Buna, Screen	A0
Viton, Screen	W0
Buna, Screen, Override, Knob	B5
Viton, Screen, Override, Knob	V5

Note: Use screen only if flow direction is from (1) to (2).

BODIES	
Blank	Without Body
S	#12 SAE Ports

VOLTAGE	
06	6 VDC
12	12 VDC
24	24 VDC
36	36 VDC
48	48 VDC
25	24 VAC
11	120 VAC
22	220 VAC
44	440 VAC

"D" COIL TERMINATION

(All DC Except as Noted)

DL	Double Lead
DT	Deutsch on Leads DT04-2P
MI	Metri-Pack on Leads
PI	Packard on Leads
WL	Weatherpack on Leads

SS	Single Spade
DS	Double Spade
HC	DIN 43650 (Hirschmann) – (AC & DC)
CL	Conduit Lead – (AC Only)
DI	Deutsch - Integral DT04-2P

IA	"I" Coil AMP Superseal - Integral
ID	"I" Coil Deutsch – Integral DT04-2P
IJ	"I" Coil AMP Jr. Timer - Integral
IM	"I" Coil Metri-Pack - Integral

IMMERSION PROOF "D" TYPE

Approximate Coil Weight: .74 lbs/.33 kg.